

# 9102

EpXylon 9102 'Quick-Fix' Putty



## 'Quick-Fix' Putty

- Super fast curing, steel filled polymer putty for dependable emergency repairs
- Mixes and applies easily, and cures in temperatures as low as 4°C
- Excellent resistance to oil, gasoline, water and many chemicals

TRUST EpXylon FOR Ease of Application  
Wide Versatility  
Outstanding Physical Properties

**MAGNA INDUSTRIAL CO. LIMITED**  
Total Quality Maintenance



## SPECIAL FEATURES

**EpXylon 9102** is a steel filled polymer putty for quick and dependable emergency repairs of damaged equipment and machinery.

- **EpXylon 9102** has excellent resistance to oil, gasoline, water and many chemicals, allowing the cured areas to function normally.
- **EpXylon 9102** is most suitable for repairing and rebuilding in areas where welding is undesirable or impossible.
- **EpXylon 9102** can be drilled, tapped, sanded, machined or painted after curing.
- **EpXylon 9102** bonds to steel, iron, aluminium, brass, wood and concrete, permitting it to have a wide application range.

## OUTSTANDING PROPERTIES

**EpXylon 9102** is an ultra-quick steel filled polymer putty that :


- cures in less than 1 hour.
- can be applied easily in temperatures as low as 4°C.
- is formulated to be a dense mix that can be applied easily to overhead and vertical surfaces without running or sagging.
- provides an excellent colour match on steel.

## USE FOR

**EpXylon 9102** is perfect for quick and emergency repairing of cracks and breaks.

Use **EpXylon 9102** to :

- repair cracks and breaks in equipment, machinery, or castings
- patch and rebuild blow holes and pits in castings
- rebuild worn equipment
- rebuild pump and valve bodies



Magna Industrial reserves the right to modify or change this product for purposes of improving its performance characteristics.  
© 2002 Magna Industrial Co. Limited.

™ - The EpXylon™ trade mark is the property of Magna Industrial Co. Limited and its associated companies

**MAGNA INDUSTRIAL CO. LIMITED**  
Total Quality Maintenance