



## Technical Datasheet

---

# RT-177 Penetrant

### Properties

- penetrates rust and copper rust
- immediate effect
- extra penetrating
- may be used on wet surfaces
- non-corrosive
- acid-free

### Description

RT-177 with penetrating and lubricating properties for the dismounting of rustbound nuts, bolts, valve assemblies, clutches etc.

RT-177 is used in all kinds of industries. The penetrating properties enables immediate and optimum effect.

The product is also available in 5 and 25 litres.



**ITW Chemical Products Scandinavia**

Priorsvej 36 • 8600 Silkeborg • Phone.: +45 86 82 64 44 • Fax: +45 86 82 64 64 •  
e-mail: [info@itw-scan.dk](mailto:info@itw-scan.dk) • [www.itw-scan.dk](http://www.itw-scan.dk)

Important note: All information and technical data are based on tests which to our knowledge are correct and reliable. However, there are no guarantees. It is the responsibility of the user to make sure that the information is useable and complete in connection with the purpose in question.

Date: 05.05.2003

INFORMATION

# RT-177 Penetrant

## Technical and physical data

Item no.	18715
Packaging	aerosol
Contains	500 ml
Weight	380 g
Propellant	propane/butane
Base	acid free mineral oil
Additive	rust preventing
Flashpoint (concentrate)	177°C
Density at 15°C	0,750 g/cm <sup>3</sup>
Boiling point	>180°C
Viscosity	36 cSt
Emptying rate	2,26 g/sec

## Information

For more technical information and Material Safety Datasheets for the products at ITW, please contact:

***ITW* Chemical Products Scandinavia**

*Priorsvej 36  
8600 Silkeborg  
Tlf.: (+45) 86 82 64 44  
Fax: (+45) 86 82 64 64  
e-mail: [info@itw-scan.dk](mailto:info@itw-scan.dk)  
[www.itw-scan.dk](http://www.itw-scan.dk)*