



Technical Datasheet

US-45 Universal MRO Oil

INFORMATION

Description

US-45 Universal MRO Oil can be used as a multipurpose product with lubricating, rust dissolving, protecting and moisture repellent properties. It can be used on all types of machinery.

US-45 Universal MRO Oil cleans, protects and lubricates all kinds of metal parts and is safe to use on most surfaces including plastic and rubber.

Fast acting rust dissolver is perfect for the dismounting of rustbounded nuts, bolts, valves etc.

US-45 Universal MRO Oil is a high performance penetrating lubricant, that leaves a light lubricating oil film. The product protects wires, brakeparts, gear wheels, locks, tools etc.

US-45 Universal MRO Oil is a low viscosity lubricant which is invaluable for penetrating and lubricating inaccessible areas.

US-45 Universal MRO Oil has excellent moisture repellent properties and is safe to use on batteries, starters and cables. Protects all metal parts exposed to moisture and water. Re-establish contact. Start problems and leak current are avoided.

Excellent corrosion protecting properties that leave a protecting film for short-term, indoor storage. The product cleans tarnished and lustreless metals and prevents additional listlessness. US-45 Universal MRO Oil removes dirt, soot, grease, tar and film. US-45 Universal MRO Oil is silicone- and resin-free and will not create accumulation.

Properties

- lubricating/penetrating, cleaning
- rust dissolving, moisture repellent
- re-establish contact
- corrosion inhibiting
- removes unpleasant sounds
- no deteriorating effect on plastic/rubber
- cleaning effect

Manufactured by :

ITW Chemical Products Scandinavia

Distributed by Magna Industrial Co. Limited, Hong Kong
Telephone : (852) 25775187 Fax (852) 25773190 Email magna@magnagroup.com

Important note: All information and technical data are based on tests which to our knowledge are correct and reliable. However, there are no guarantees. It is the responsibility of the user to make sure that the information is useable and complete in connection with the purpose in question.

US-45 Universal MRO Oil

Technical and physical data

Part number	CK 018455
Packing	spray can 500ml
Weight	368 g
Propellant	propane/butane
Colour	clear/transparent
Odour	mild/fresh
Base	hydrocarbons
Density at 15°C	0.71 g/cm ³
Water soluble	<0.30 weight%
Temperature limit	from -25°C to aprox +125°C
Valve	Replaceable
Flashpoint	57°C
Emptying rate	0.796 g/sec.

Information

For further details/enquires email to magna@magnagroup.com

Manufactured by :

ITW Chemical Products Scandinavia

Distributed by Magna Industrial Co. Limited, Hong Kong
Telephone : (852) 25775187 Fax (852) 25773190 Email magna@magnagroup.com